

## MINIMUM SPECIFICATIONS FOR BOSS RX70

Quantity of one (1) Boss model RX70 portable air compressor (s) to include the following as standard equipment:

### **COMPRESSOR:**

- Boss oil-flooded, rotary screw air-end designed to produce up to 70 CFM @ 100 PSIG continuously.
- Two-year warranty on the air-end.
- Air/Oil reservoir with filler port and sightglass.
- Self-contained separator element with easy access spin-on housing.
- Aerodynamically designed cooling package with automatic thermal sensing control to ensure proper operating temperatures.
- Replaceable spin-in compressor lubricant filter with safety bypass and 25 micron rating.
- Dry-type air intake filter with replaceable element.
- Instrumentation to include: compressor temperature gauge, hourmeter and air pressure gauge, keyed off /on switch, override button and choke.
- Safety devices to include: minimum pressure device, compressor lube hi-temp, automatic blowdown device, high-pressure relief valve, and necessary warning and information decals.
- Two-wheel with rotatable caster with hinged handle bar for easy mobility.
- Ambient operating temperature range -20°F to 105°F
- 5.2 Gallon fuel tank.
- Qty. (1), ½" air service valve connection (NPT)
- Operation, parts, and maintenance manual.

Revised: 2/2008  
Supersedes:

Specifications subject to change without notice

***ENGINE:***

- HONDA “GX670U” 24 Hp, 4-cycle, v-twin, overhead valve, air-cooled gasoline engine.
- Standard Honda engine warranty.
- Electronic ignition for broad RPM response.
- Electric solenoid shift starter and pull start.
- Overhead valve design for greater fuel efficiency and lower emissions.
- In line fuel filter.
- Oil fill in valve cover.
- Low oil level switch with safety shutdown.
- Muffler heat shield & guard.
- 20 amp charging system.